

# 21 JOULE XENON BEACONS

## Exd(e), Weatherproof XB4 Range



### Introduction

These **high output (21 Joule)** beacons have been designed for use in potentially explosive atmospheres and harsh environmental conditions. The marine grade alloy or stainless steel enclosures are suitable for use offshore or onshore, where light weight combined with corrosion resistance and strength is required. Units can be painted to customer specification and fitted with identification labels.

Available with optional Exe terminal chamber.

- ★ Zone 1 and Zone 2 use.
- ★ Exde IICT5.
- ★ ATEX approved Ex II 2GD.
- ★ BASEEFA certified.
- ★ UL Listed for USA and Canada
  - Hazardous locations:
    - Class I, Div 1, Groups C & D.
    - Class I, Zone 1, AExd IIB T4.
  - Ordinary locations: Visual-Signal Device.
- ★ GOST 'R' Certified.
- ★ Brazilian (Inmetro) Certified.
- ★ Australian (SAA) certified.
- ★ \*Certified temperature  $-55^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$ .
- ★ IP67 and IP66.
- ★ Stainless steel or marine grade alloy.
- ★ Various lens colours.
- ★ Twin replaceable tubes.
- ★ Exde version has gland earth continuity in the GRP terminal chamber.
- ★ Tapered spigot flamepath.
- ★ Telephone or relay initiated option.
- ★ Optional lens guard.
- \*Depending on version.

Cooper MEDC Ltd, Colliery Road,  
Pinxton, Nottingham NG16 6JF, UK.  
Tel: +44 (0)1773 864100  
Fax: +44 (0)1773 582800

Cooper MEDC (USA) 3413 North Sam Houston Parkway,  
West, Houston, Texas 77086, USA.  
Tel: +1 (713) 937 9772  
Fax: +1 (713) 937 9773

Sales Enq. Fax: +44 (0)1773 582830 Sales Orders Fax: +44 (0)1773 582832  
E-Mail: [medc.sales@cooperindustries.com](mailto:medc.sales@cooperindustries.com) Web: [www.medc.com](http://www.medc.com)



